

Integrated amplifier



Get into the music
ZAX - 60

The first step in building up a real audiophile reproduction chain, coming directly from his mighty brother ZAX-120, offering the same sonic, electrical and mechanical performance. Only the power is a bit less...



Powerfull of Passion
ZAX-120

Official & Gentleman within Amplifier class: power and graceful. Equipped with five switched line input, high quality gold plated relays featured, to keep unchanged original musical signal throughout in/out path. Advanced technology BJT's take care of the most demanding speaker system.



Discovering details
ZXT - 60

All new hybrid integrated amplifier, Lector introduce the first hybrid integrated amplifier in 1982. New technology as lexan power mosfet with automatic bias control, hi current output and gentle giant sound quality. All Lector experience as inventor of integrated hybrid technology!

VFI-700 Hybrid phono mm/line integrated amplifier



This device is the mirror image of the hybrid amplifier topology. Provided with vacuum tube phono MM input is capable of the highest Performances.

Lector research develop over more than 20 years, is reflected into VFI-700 design !.

Phono riaa stages



Lector Fonix mm/mc solid state

Made by two separated circuits for MM and MC cartridge. Two turntables are allowed to be connected at the same time. MM-MC input provided with RCA resistite terminations for Impedante matching. All components are premium Grade quality: film & foil cap's with low noise and high precision, low resistance power supply in shunt configuration for better sound quality !



Lector Phono Amp mm tube preamp

Vacuum tube phono riaa preamplifier with passive equalization circuits, two double triode in pure class A with Lector original technology as control optical bias for natural sound reproduction. No overall feedback network, premium grade components, direct input to the tube from MM cartridge without coupling capacitors, low impedante output.



Lector Phono Amp System mm/mc tube preamp

MM & MC phono cartridge amplification and equalization circuits share the same chassis. External power supply unit optimize S/N ratio. Provided with resistite RCA terminations for MC matching inputs performances. Two separate inputs for MC and MM cartridge. Exclusive Lector technology as optical bias tubes control. Pure class A circuits as five double triode tube.



CDP-7 mkIII / PSU-7
Reference cd player system



Digicode S-192

Digital to analog convertor hi resolution with USB full speed input

24 bit / 192 khz

5 digital inputs / separate power supply unit

www.lector-audio.com
www.lector-audio.it

Handcrafted in Italy EEC

MODEL	TYPE	INPUT OUTPUT	DISTORSION %THD	DAMPING FACTOR	FREQUENCY RESPONSE <1db	OUTPUT RMS POWER	OUTPUTS CONNECTOR	SPEC'S DATA
ZAX-60	SOLID STATE INTEGRATED AMPLIFIER BJT OUTPUT TECHNOLOGY	5 LINE 2 REC OUT 1 PASSIVE VOLUME OUTPUT	< 0.01%	> 100	20 - 50 khz	60 W / 8 OHM 90 W / 4 OHM	ALL GOLD PLATED CONNECTORS	400 (L) x 105 (H) x 300 (D)mm KG.6.5 NET 50/60 HZ 220 V/A 110/230 V-AC
ZAX-120	SOLID STATE INTEGRATED AMPLIFIER BJT OUTPUT TECHNOLOGY	5 LINE 2 REC OUT 1 PASSIVE VOLUME OUTPUT	< 0.1%	> 100	20 - 50 khz	120W/8 OHM 180 W/4 OHM	ALL GOLD PLATED CONNECTORS	400 (L) x 100 (H) x 400 (D)mm KG.9 NET 50/60 HZ 250 V/A 110/230 VAC
ZXT-60	HYBRID MOSFET INTEGRATED AMPLIFIER LEXAN MOSFET	5 LINE 2 REC OUT 1 PASSIVE VOLUME OUTPUT	< 0.1%	> 100	20- 50 khz	60 W / 8 OHM 90 W / 4 OHM	ALL GOLD PLATED CONNECTORS	400 x (L) x 105 (H) x 300 (D)mm KG.11 NET 50/60HZ 280 V/A 110/230 VAC
VFI-700	HYBRID MOSFET INTEGRATED AMPLIFIER PHONO MM INPUT	3 LINE 1 PHONO MM 1 REC OUT 1 PASSIVE VOLUME OUTPUT	< 0.1%	> 100	20 - 50 khz	50 W / 8 OHM 80 W / 4 OHM	ALL GOLD PLATED CONNECTORS	400 (L) x 100 (H) x 300 (D)mm KG.12 NET 50/60 HZ 205 V/A 110/230 V-AC

MODEL	TYPE	PHONO INPUT	DISTORSION %THD	TOTAL GAIN IN / OUT (db)	FREQUENCY RESPONSE <1db	OUTPUT IMPEDANCE	OUTPUTS CONNECTOR	SPEC'S DATA
Phono amp MM	CLASS A M M TUBE PHONO RIAA ADAPTOR PREAMPLIFIER	1.5 mV 47 kohm 100 pf	< 0.1%	45 db	20 - 20 khz	290 ohm 10 volt max	GOLD PLATED MAIN RCA	400 (L) x 85 (H) x 300 (D)mm KG.6.5 NET 50/60 HZ 35 V/A 110/230 V-AC
Phono AMP System W/PSU	CLASS A M M MC TUBE PHONO RIAA ADAPTOR PRE	MM:1.5mV 47K /100pf MC: 0.4mV 150ohm	< 0.1%	MM: 45 db MC: 62 db	20 - 20 khz	290 ohm 10 volt max	GOLD PLATED MAIN RCA	400 (L) x 80 (H) x 300 (D)mm KG.7 NET PSU :225x85x300 50/60 HZ 50 V/A 110/230 VAC
VPP 02 / MMC tube pre pre	CLASS A pre tube phono preamplifier for M C cartridge	0.4-0.6mV 47 kohm 1500 pf	< 0.1%	22 db	20- 20 khz	1 kohm 10 volt max	GOLD PLATED MAIN RCA	220 x (L) x 80 (H) x 300 (D)mm KG.2 NET WITH PSU ADAPTOR 10 V/A 50/60HZ 110/230 VAC
FONIX (SOLID STATE)	CLASS A M M M C Input riaa	MM:1.5mV 47K /100pf MC: 0.4mV 150ohm	< 0.1%	MM: 45 db MC: 62 db	20 - 20 khz	100 ohm 10 volt max	GOLD PLATED MAIN RCA	400 (L) x 85 (H) x 300 (D)mm KG.6.5 NET 50/60 HZ 35 V/A 110/230 V-AC